

Accelerate your digital transformation journey **fi-8150**

The fi-8150 front-office scanner for light workloads employs innovative feeding and Clear Image Capture technology to deliver industry-leading reliability.



Image Quality

Clear Image Capture (CIC) technology resets the benchmark for high quality image capture, by combining the reliability and flexibility of Contact Imaging Sensor (CIS) hardware, with an industry-leading, image processor. CIC technology delivers precise, crisp images, and industry-leading OCR accuracy rates while also removing unwanted watermarks and artifacts.

Paper Feeding

Evolved paper handling with a large 100-page hopper, an all-wheel drive mechanism, and fast 100 images captured per minute, make the fi-8150 one of the easiest and most efficient scanners to operate. The patented Automatic Separation Control uses state of the art technology to sense paper weights and adjusts to consistently separate documents and provide the perfect feed, ensuring documents are safely captured.

Reliability

The fi-8150 is built to last and powers up every time you need it regardless of job size. Strong urethane rollers, heavy duty motors, a sturdy frame, and durable consumables combine for a long-lasting scanner that will let your organization capture the volumes of paper from seasonal peaks and heavy backlogs, worry free. Backed by Ricoh's US-based, legendary solutions architects and support teams.



PaperStream IP

Compatible with all major document management software packages, PaperStream IP (PSIP) is a TWAIN/ISIS® compliant driver that cleans up and optimizes scanned images without any configuration.

PaperStream Capture

Take advantage of powerful indexing and sorting features, putting the document in the right location for great organization and fast retrieval. Now includes both 2D and 1D barcode support in the box.

PaperStream Clickscan


Easy to use capture software for any business. Simple scanning interface with 3-steps: scan, select destination, and save.

Flexible connectivity options

Choose between PaperStream IP Net for flexible, adaptable capture architectures, and PaperStream NX Manager for centralized, server-based capture.

The next generation in scanning excellence

fi-8150 Image Scanner



Technical Information

Scanner Type	ADF (Automatic Document Feeder) / Manual Feed, Duplex	Power Consumption	Operating Mode: 21 W or less / 17 W (Eco mode) Sleep Mode: 2.0 W or less (LAN) / 1.4 W or less (USB) Auto Standby (Off) Mode: 0.2 W or less
Scanning Speed*¹ (A4 Portrait) (Color / Grayscale* ² / Monochrome* ³)	Simplex: 50 ppm (200/300 dpi) Duplex: 100 ipm (200/300 dpi)	Operating Environment	Temperature: 41 to 95 °F (5 to 35 °C) Relative Humidity: 15 to 80% (non-condensing)
Image Sensor Type	CIS x 2 (front x 1, back x 1)	Environmental Compliance	ENERGY STAR®, RoHS
Light Source	RGB LED x 2 (front x 1, back x 1)	Dimensions*¹⁵ (Width x Depth x Height)	11.8 x 6.7 x 6.4 in. (300 x 170 x 163 mm)
Optical Resolution	600 dpi	Weight	8.8 lb (4 kg)
Output Resolution*⁴ (Color / Grayscale / Monochrome)	50 to 600 dpi (adjustable by 1 dpi increments) 1,200 dpi (driver)* ⁵	Supported Operating System	Windows® 11, Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2022, Windows Server® 2019, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008 R2, macOS, Linux (Ubuntu)
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit	Included Software / Drivers	PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver* ¹⁵ , Image Scanner Driver for macOS (ICA)* ^{15*16} , Image Scanner Driver for Linux (SANE)* ^{15*16} , PaperStream Capture, PaperStream ClickScan* ¹⁶ , Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap™* ¹⁶ , Scanner Central Admin
Background Colors	White/Black (selectable)	Image Processing Functions	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Drop-out color (None/Red/Green/Blue/White/Saturation/Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge filler, Vertical streaks reduction, Background pattern removal, Cropping, Static threshold
Document Size	Maximum* ⁶ : 8.5 x 14 in. (215.9 x 355.6 mm) Minimum: 1.9 x 2 in. (48x50 mm) Long Page Scanning* ⁷ : 240 in. (6,096 mm)	Included Items	ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM
Paper Weight (Thickness)	5.3 to 124 lb (20 to 465 g/m ²)* ⁸	Standard Model	PN: PA03810-B105
Paper	0.276 in. (Less than 7 mm)* ⁹	Certifications	Tungsten® VRS Elite
Booklet	0.055 in. (1.4 mm) or less* ¹⁰	Warranty	1 Year Advance Exchange
Plastic Card			
ADF Capacity*¹¹ *¹²	100 sheets (Letter 20 lb or A4 80 g/m ²)		
Expected Daily Volume*¹³	8,000 sheets		
Multifeed Detection	Overlap detection (Ultrasonic sensor) Length detection		
Paper Protection	Image monitoring		
Interface			
USB	3.2 Gen 1x1 / USB 2.0 / USB 1.1		
Ethernet	10BASE-T, 100BASE-TX, 1000BASE-T		
Power Requirements	AC 100 to 240 V 50/60Hz		

Service Programs & Options

Advance Exchange	S8150-AEMYNBD-1 S8150-AEMYNBD-3 S8150-AEMYNBD-5	One, three or five year programs offer whole-unit, next business day replacement for scanner equipment*	Ricoh's industry-leading support keeps digital transformation projects on-time and on budget
PaperStream Capture Pro	PSCP-WG-0001	PaperStream Capture Pro Workgroup software license	• U.S. based support
Depot Mail-in Repair	S8150-DEPW5DY-3	3-year scanner contract provides mail-in unit repair that includes spare parts, labor, and one-way shipping to customer	• Specialized Teams • Flexible service programs

Consumables & Options

Imprinter	PA03810-D201	Prints a string of characters on document after a scan
Print Cartridge	CA00050-0262	Lifetime: approx. 4,000,000 printed characters
Brake Roller	PA03810-0001	Lifetime: approx. 200,000 sheets or 1 year
Pick Roller	PA03670-0002	Lifetime: approx. 200,000 sheets or 1 year
ScanAid Kit	CG01000-302801	Consumable kit with instructions and cleaning supplies
Carrier Sheets	PA03360-0013	Pack of 5 Sheets
	PA03770-0015	Pack of 3 Sheets
	PA03810-0020	Pack of Single Sheet



*¹ Actual scanning speeds may vary with data transmission and software processing times. *² Indicated speeds are from using JPEG compression. *³ Indicated speeds are from using TIFF CCITT Group 4 compression. *⁴ Selectable maximum resolution may vary depending on the length of the scanned document. *⁵ Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *⁶ Maximum document width possible for scanning is 240 mm (9.5 inch). *⁷ For use with PaperStream NX Manager, the maximum resolution supported is 400 dpi, with maximum lengths ranging with resolution. Simplex: 1,828.8 mm (72 in.) [below 300 dpi], 355.6 mm (14 in.) [below 400 dpi]. Duplex: 863.6 mm (34 in.) [below 300 dpi], 355.6 mm (14 in.) [below 400 dpi]. *⁸ Thicknesses of up to 128 to 209 g/m² (34 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 inch) sizes. *⁹ Booklet scanning requires use of Booklet Carrier Sheets. Indicated thickness is inclusive of Booklet Carrier Sheet thickness. *¹⁰ Continuous feeding is supported when scanning up to 10 unembossed cards with thicknesses of 0.76 mm or less. *¹¹ Maximum capacity depends on paper weight and may vary. *¹² Capable of setting additional documents while scanning. *¹³ Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. *¹⁴ Excludes the ADF paper chute and stacker. *¹⁵ Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for macOS/Linux or WIA Driver. *¹⁶ Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions. www.pfu-us.ricoh.com.

*Replacement units shipped overnight for all requests received by 2 P.M. PST, Monday-Friday

Trademarks

ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Safety Precautions

Please carefully read the safety precautions prior to the use of this device and follow the recommended instructions for correct use. Do not place this device in wet, moist, highly humid, dusty or oily areas. Use of this device under such conditions may result in electrical shock, fire or damage to the device. Please use this device within the power ratings listed.

ENERGY STAR®

ENERGY STAR® PFU Limited has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.



To learn more, visit us at www.RicohDocumentScanners.com or contact us at (888) 425-8228.

Copyright © 2024 PFU America, Inc. All other trademarks are the property of their respective owners.

V1_fi8170_033124