

Accelerate your digital transformation journey

fi-8270

Made for demanding workflows, the fi-8270 employs innovative feeding and Clear Image Capture technology to deliver industry-leading reliability. The flatbed provides even more utility, making it possible to scan specialty documents and bound periodicals.



### **Image Quality**

Clear Image Capture (CIC) technology resets the benchmark for high quality image capture, by combining the reliability and flexibility of Contact Imaging Sensor (CIS) hardware with an industry-leading image processor. CIC technology delivers precise, crisp images and industry-leading OCR accuracy rates while also removing unwanted watermarks and artifacts.

### **Paper Feeding**

Evolved paper handling with a large 100-page hopper, an all-wheel drive mechanism, and fast 140 images captured per minute, make the fi-8270 one of the easiest and most efficient scanners to operate. The patented Automatic Separation Control uses state of the art technology to sense paper weights and adjusts to consistently separate documents and provide the perfect feed, ensuring documents are safely captured.

### Reliability

The fi-8270 is built to last and powers up every time you need it regardless of job size. Strong urethane rollers, heavy duty motors, a sturdy frame, and durable consumables combine for a long-lasting scanner that will let your organization capture the volumes of paper from seasonal peaks and heavy backlogs, worry free. Backed by Ricoh's US-based, legendary solutions architects and support teams.



### PaperStream IP

Compatible with all major document management software packages, PaperStream IP (PSIP) is a TWAIN/ISIS® compliant driver that cleans up and optimizes scanned images without any configuration.

## PaperStream Capture

Take advantage of powerful indexing and sorting features, putting the document in the right location for great organization and fast retrieval. Now includes both 2D and 1D barcode support in the box.

## PaperStream Clickscan

Easy to use capture software for any business. Simple scanning interface with 3-steps: scan, select destination, and save.

# Flexible connectivity options

Choose between PaperStream IP Net for flexible, adaptable capture architectures, and PaperStream NX Manager for centralized, serverbased capture.

# The next generation in scanning excellence fi-8270 Image Scanner















#### **Technical Information**

ADF (Automatic Document Feeder) / Manual Feed, Scanner Type Flatbed, Duplex

Scanning Speed\*1 ADF Simplex: 70 ppm (200/300 dpi) (A4 Portrait) (Color / Grayscale\*2

Duplex: 140 ipm (200/300 dpi / Monochrome\*3) Flatbed 1.7 seconds (200/300dpi)

Image Sensor Type CIS x 2 (front x 1, back x 1) Flatbed: Color CCD x1

**Light Source** ADF: RGB LED x 2 (front x 1, back x 1)

Flatbed: White LED

**Optical Resolution** 600 dpi

Output Resolution\*4 50 to 600 dpi (adjustable by 1 dpi increments)

1,200 dpi (driver)\*5 (Color / Grayscale /

Monochrome)

**Output Format** Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit

**Background Colors** White/Black (selectable)

Flatbed: WHite (or optional black)

**Document Size** 

Maximum\*6 8.5 x 14 in. (215.9 x 355.6 mm) ADF 1.9 x 2 in. (48x50 mm) Minimum

Long Page Scanning\*7 240 in. (6.096 mm) 8.5 x 11.7 inch (215.9 x 297 mm) Flatbed Maximum

Paper Weight (Thickness)

5.3 to 124 lb (20 to 465 g/m<sup>2</sup>)\*8 Paper Booklet 0.276 in. (Less than 7 mm)\* 0.055 in. (1.4 mm) or less\*10 Plastic Card

ADF Capacity\*11 \*12 100 sheets (Letter 20 lb or A4 80 g/m<sup>2</sup>)

Expected Daily Volume\*13 10,000 sheets

Multifeed Detection Overlap detection (Ultrasonic sensor)

Paper Protection Image monitoring, Sound detection (iSOP)\*14

Interface

3.2 Gen 1x1 / USB 2.0 / USB 1.1 USB Ethernet 10BASE-T, 100BASE-TX, 1000BASE-T

AC 100V to 240V 50/60Hz **Power Requirements** 

**Power Consumption** 

Operating Mode 28 W or less / 17 W (Eco mode) Sleep Mode 2.0 W or less (LAN) / 1.4 W or less (USB)

Auto Standby (Off) Mode 0.2 W or less

Operating Environment

41 to 95 °F (5 to 35 °C) Temperature Relative Humidity 15 to 80% (non-condensing)

Environmental Com-

pliance

ENERGY STAR®, RoHS

Dimensions\*15

(Width x Depth x Height) 11.8 x 22.7 x 9.2 in. (300 x 577 x 234 mm)

Weight 19.4 lb (8.8 kg)

Supported Operating Windows® 11. Windows® 10. Windows® 8.1.

Windows® 7, Windows Server® 2022, Windows Server® 2019, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows

Server® 2008 R2, Linux (Ubuntu)

Included Software /

Drivers

PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver\* 16, Image Scanner Driver for Linux (SANE)\*16\*17 PaperStream Capture, PaperStream ClickScan\*<sup>17</sup>, Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap™\*<sup>17</sup>,

Scanner Central Admin

**Image Processing** Functions

Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/ Blue/White/Saturation/Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge filler, Vertical streaks reduction,

Multi image output, Automatic color detection,

Background pattern removal, Cropping, Static threshold.

Included Items ADF paper chute, AC cable, AC adapter, USB cable,

Setup DVD-ROM

**Trade Compliant** 

Standard Model PN: PA03810-B555 Certifications Tungsten® VRS Elite Warranty 1 Year Advance Exchange

### **Service Programs & Options**

1-Year Advance Exchange S8270-AEPWNBD-1 3-Year Advance Exchange S8270-AEMYNBD-3 S800R-AEMYNBD-5 5-Year Advance Exchange S8270-DEPW5DY-3 Depot Mail-in Repair

One, three or five year programs offer whole-unit, next business day replacement for scanner equipment\*

> 3-year scanner contract provides mail-in unit repair that includes spare parts, labor, and one-way shipping to customer

Ricoh industry-leading support keeps digital transformation projects on-time and on budget

U.S. based support

Specialized Teams

• Flexible service programs

### Consumables & Options

Lifetime: approx. 200,000 sheets or 1 year **Brake Roller** PA03810-0001 Pick Roller PA03670-0002 Lifetime: approx. 200,000 sheets or 1 year CG01000-302801 Consumable kit with instructions and cleaning supplies ScanAid Kit Booklet Carrier (1Piece) PA03810-0020 Supplemental protection for items such as passports Supplemental protection for delicate items Carrier Sheets (5 Pieces) PA03360-0013 PA03810-D301 Black back flatbed cover for cropping Black Document Pad







\*1 Actual scanning speeds may vary with data transmission and software processing times. \*2 Indicated speeds are from using JPEG compression. \*3 Indicated speeds are from using TIFF CCITT Group 4 compression. \*4 Selectable maximum resolution may vary depending on the length of the scanned document. \*5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). \*6 Maximum document width possible for scanning is 240 mm (9.5 inch). \*7 For use with PaperStream NX Manager, the maximum resolution supported is 400 dpi, with maximum lengths ranging with resolution. Simplex: 1,828.8 mm (72 in.) [below 300 dpi]. \$55.6 mm (14 in.) [below 400 dpi]. \$55.6 mm (14 in.) [below 400 dpi]. \$87 linkinesses of up to 128 to 209 g/m (24 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 inch) sizes. \*9 Indicated thickness is inclusive of Booklet Carrier Sheet thickness when using the Carrier Sheets. \*10 Continuous feeding is supported when scanning up to 10 unembossed cards with thicknesses of 0.76 mm or less. \*11 Maximum capacity depends on paper weight and may vary. \*12 Capable of setting additional documents while scanning. \*13 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. \*14 Intelligent Sonic Paper Protection. \*15 Excludes the ADF paper protection. \*15 Excludes the ADF paper protection functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for Linux or WIA Driver. \*17 Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions. www.pfu-us.ricoh.com.

ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Please carefully read the safety precautions prior to the use of this device and follow the recommended instructions for correct use. Do not place this device in wet, moist, highly humid, dusty or oily areas. Use of this device under such conditions may result in electrical shock, fire or damage to the device. Please use this device within the power ratings listed.

ENERGY STAR® PFU Limited has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Specifications are subject to change without notice.

